PETROMİR
Endüstriyel Yağlar Sanayi ve Ticaret A.Ş.

PETROMIR SN SERIES

The Petromir SN series are high-quality oils formulated from high-quality base oils obtained through modern refining. They have a wide range of applications. Process oils enter the final product formulation and directly affect product performance. Therefore, their selection is crucial

USES

It is used as a raw material in plastic, rubber, chemical, agricultural, and paint production, as well as in industrial mineral oils.

Technical Specifications

TEST	METHOD	TYPICAL PROPERTIES				
		SN 100	SN 150	SN 500	SN 900	Bright Stock
Kinematic Viscosity (40°C) [cSt]	ASTM D 445	15,8-24,9	29,2-34,6	85,5-117,5	288-352	500,0-648,0
Kinematic Viscosity (100°C) [cSt]	ASTM D 445	3,2-4,5	4,9-5,8	9,8-12,2	20,5-27,5	32,0-36,0
Viscosity Index	ASTM D 2270	90-108	90-108	90-105	85-100	85-105
Flash Point,°C	ASTM D92	180-210	200-220	230-260	230-280	260-360
Pour Point,°C	ASTM D97	Max. -7	Max. -7	Max. -7	Max. -5	Max. -5
Color (ASTM)	ASTM D1500	0,5-1,5	0,5-2,5	2,0-3,5	3,0-6,0	3,0-7,0
Water Amount, PPM	ASTM D6304	Max. 70	Max. 70	Max. 70	Max. 120	Max. 150
Density ,15°C	ASTM D 4052	0,85-0,87	0,86-0,88	0,87-0,89	0,88-0,90	0,88-0,92

Yenişehir Mahallesi, Ankara Caddesi, No:405
360 Office, Kat:5/133 Pendik/İstanbul
www.petromir.com.tr
info@petromir.com.tr
+0 216 519 52 36